



Standard Accessories:	
Name	Quantity
FIM-12-4 (400X) or FIM-12-2 (200X) Bench-top Fiber Microscope	1pc
8/10.4 inch LED display	1pc
1.25mm tip for 1.25mm connectors, LC/PC, MU/PC	1pc
2.5mm tip for 2.5mm connectors, SC/PC, FC/PC, ST/PC	1pc
12V Power Cord (BNC output)	1pc
5-pin aviation connector/BNC Connector	1pc
Optional Accessories:	
Name	Quantity
USB Function	1pc
Pass/Fail Software	1pc
Optional Tips for FIM-12 Fiber Microscope	
Name	Quantity
LC-PC-M (For LC/PC connector)	1pc
MU-PC-M (For MU/PC connector)	1pc
SC-APC-M (For SC/APC connector)	1pc
FC-APC-M (For FC/APC connector)	1pc
LC-APC-M (For LC/APC connector)	1pc
2.5M-APC (For 2.5mm connectors, SC/APC, FC/APC, ST/APC)	1pc
1.25APC-M ( (For 1.25mm connectors, LC/APC, MU/APC)	1pc



## FIM-17 Fiber Microscope

- WiFi and USB connection to smartphone and PC
- Pass/Fail Analysis to IEC 61300-3-35 (only for PC software)
- Several tips available (Both female and male tips)
- Support saving inspected images and reports
- Real-time report in field through smartphone

Items	Specifications
Magnification	400X
Resolution	<1.0μm
Field of View	X: 0.3487mm Y: 0.2632mm
Laser Source	Blue LED
Focus Method	Unidirectional manual
Focus Time	1~5 seconds
Snapshot Button	yes
WiFi and USB Switch Button	yes
Communication Port	Micro USB
Connection Standard	WiFi 802.11 and USB2.0
Wireless Frequency	2.4GHz
Wireless Transmission Distance	20m
Smartphone Compatibility	Android 4.4 and above; IOS 8.0 and above
Voltage	5V
Battery	3100mAh Lithium battery
Charging Time	≤5h
Items	Specifications
Testing Time	≥5h
Dimension	19*5*3cm
Weight	0.175kg
Working Temperature	-10°C~50°C
Storage Temperature	-20°C~60°C
Humidity	<90% (non-condensing)
<b>Standard Accessories:</b>	
FIM-17 Fiber Microscope	1pc
SC-PC-F/M (For SC-PC male adapter and female adapter)	1pc
FC-PC-P/M (For FC-PC male adapter and female adapter)	1pc
LC-PC-F/M (For LC-PC male adapter and female adapter)	1pc
USB cable	1pc